QuickField simulation report

Temperature distribution in the conducting sheet

The voltage is applied to the sides of conducting sheet.



This automatically generated document consists of several sections, which specify the problem setup and finite element analysis simulation results. Navigation links in the top of each page lead to corresponding sections of this report.

Problem description and QuickField simulation files: https://quickfield.com/advanced/conducting_sheet_temperature.htm

Problem info

Problem type: Steady-State Heat Transfer Geometry model class: Plane-Parallel Problem database file names:

- Problem: Coupl5HT.pbm
- Geometry: *Coupl5.mod*
- Material Data: Coupl5ht.dht
- Material Data 2 (library): none
- Electric circuit: none

Results taken from other problems:

• Generated Heat: Coupl5cf.pbm

Geometry model



Table 1. Geometry model statistics

	With Label	Total
Blocks	1	1
Edges	3	7
Vertices	0	7

Number of nodes: 2488.

Labelled objects

There are following labelled objects in the geometry model (Material Data file could contain more labels, but only those labels that assigned to geometric objects are listed)



Detailed information about each label is listed below.

Labelled objects: block "bar" There are (1) objects with this label

Thermal conductivity: lambda_x=380 [W/(K*m)], lambda_y=380 [W/(K*m)] Volume heat: Q=nonlinear (see Table 2 in the "Nonlinear dependencies" section)



Labelled objects: edge "u1" There are (1) objects with this label

Convection: alpha=10 [W/(K*m2)], temperature T0=-273.15 [K]



Labelled objects: edge "side_convection" There are (5) objects with this label

Convection: alpha=10 [W/(K*m2)], temperature T0=-273.15 [K]



Labelled objects: edge "u2" There are (1) objects with this label

Convection: alpha=10 [W/(K*m2)], temperature T0=-273.15 [K]



Results

Field lines



Results

Color map of Heat flux |F| [W/m2]



Nonlinear dependencies

Table 2. Volume heat source

- T [K] Q [W/m3]
- 0 0
- 100 -2000000